# UNIGATE® CL 用于DINrail的协议转换器



符合规范

已认证

可配置的

即可使用

在德国设计和制造

## 数据手册

完整的 LONWorks 从站接口

78 kBit/s

收发器FTT-10AF

固定神经元ID

隔离的LONWorks接口，带有4针螺丝插头

通过脚本控制LONWorks变量（SNVTs和UNVTs）。不可配置。

多达512字节的输入和512字节的输出数据（总共多达62个输入和输出SNVTs）

RS232/RS485/RS422最高625 kBaud

# 技术数据

| | |
|---|---|
| 尺寸<br>(WxDxH mm) | 23x 115x 116 (包括螺钉-插头-连接器)<br>23x 115x 100 (不包括螺钉-插头-连接器) |
| 重量 | 大约128 g |
| 保护等级 | DIN 导轨 IP20 |
| 外壳材料 | 聚酰胺 |
| 安装方式 | DIN 导轨 (EN 50022) |
| 电压供应 | 10至33伏的直流电。<br>对不正确的极性、短路和过载的保护已被整合。 |
| 电流消耗<br>(+24V/DC时) | typ. 30mA, max. 40mA |
| 工作温度 | -40° C (非冷凝) 至+85° C |
| 存储温度 | -40° C ... +85° C |
| 现场总线功能 | 所有指定的LONWorks功能 |
| 技术 | ASIC |
| 认证 | CE |
| 电镀分部 | 母线上的标准 |
| 选项 | 应用方面的电化学划分 |

## 订货信息

| 订货名称 | 描述 | 订货号 |
| --- | --- | --- |
| UNIGATE CL-LN62 | DIN-rail module with seral interface - RS232, 422 and 485 on-board - to LONWorks 62. Additional Debug-interface, Housing: sky blue RAL 5015 | V3623 |
| UNIGATE CL-GT-LN62 | DIN-rail module with seral interface - RS232, 422 and 485 on-board - to LONWorks 62. Additional Debug-interface, , Housing: sky blue RAL 5015. Additional galvanic separation RS-side (RS-Interface) | V3863 |
| Optional | Neutral version | on request |
| Optional | Customized design | on request |
| | Note: Further variants can be found in the brochure and the price list. | |